





pecincations				
		V-STROM 1050	V-STROM 1050DE	
Overall length		2,265 mm (89.2 in.)	2,390 mm (94.1 in.)	
Overall width		940 mm (37.0 in.)	960 mm (37.8 in.)	
Overall height		1,515 mm (59.6 in.)	1,505 mm (59.3 in.)	
Wheelbase		1,555 mm (61.2 in.)	1,595 mm (62.8 in.)	
Ground clearance		165 mm (6.5 in.)	190 mm (7.5 in.)	
Seat height		855 mm (33.7 in.)	880 mm (34.6 in.)	
Curb mass		242kg (534lbs)	252kg (554lbs)	
Engine type		4-stroke, liquid-cooled, DOHC, 90° V-twin		
Bore x stroke		100.0 mm x 66.0 mm (3.937 in. x 2.598 in.)		
Engine displacement		1,037cm³ (63.3 cu. ln.)		
Compression ratio		11.5:1		
Fuel system		Fuel injection		
Starter system		Electric		
Lubrication system		Wet sump		
Transmission		6-speed constant mesh		
Suspension	Front	Inverted telescopic, o	Inverted telescopic, coil spring, oil damped	
	Rear	Link type, coil spring, oil damped		
Rake / trail		25°40' / 110 mm (4.33 in)	27°30' / 126 mm (4.96 in)	
Brakes	Front	Disc	Disc, twin	
	Rear	Disc		
Tyres	Front	110/80R19M/C 59V tubeless	90/90-21M/C 54H tube type	
	Rear	150/70R17M/C 69V tubeless	150/70R17M/C 69H tubeless	
Ignition system		Electronic ignition (transistorized)		
Fuel tank capacity		20.0 L (5.3 US gal / 4.4 Imp gal)		
			* F C ch	

* European Spec. shown

Standard and optional equipment available may vary for individual markets. Please enquire at your dealers, as specifications and illustrations may refer to models not available in your region.

All photographs in this brochure were taken with relevant permission. Images of the vehicles without number plates on public roads are composite photos.







V-STROM 1050/DE Product Information 99999-A0025-221 SEP. '22







Suzuki Intelligent Ride System (S.I.R.S.)

Suzuki's robust collection of our latest electronic systems were developed to assist and help you optimize performance characteristics to match your changing riding needs and preferences. By making the V-STROM 1050/DE feel more controllable, predictable and less tiring to operate, these systems help you ride with greater confidence and peace of mind, whether touring for long distances, carrying gear, or leaving paved roads behind to explore rural trails.



This photo includes optional accessories.

6-axis IMU

Integrating accelerometers and gyroscopes into a single compact package, the 6-axis Bosch IMU measures angular rate and acceleration to constantly monitor pitch, roll, and yaw movement. This helps realize several of the latest S.I.R.S. electronic control systems.



G (Gravel) mode (V-STROM 1050DE only)

In addition to the 3 existing traction control modes (+ OFF), the V-STROM 1050DE features a new G (Gravel) mode setting that retards ignition timing and allows a limited amount of slip when riding on unpaved surfaces to help the rider better negotiate gravel roads.

Note: Because G (Gravel) mode allows a certain amount of rear tyre slip, it is not suitable for use on paved surfaces.

Rear ABS Off mode (V-STROM 1050DE only)

The V-STROM 1050DE adds the ability to switch off rear ABS for improved controllability on gravel and other unpaved surfaces. In addition, the Motion Track Brake System has been optimized for the larger front wheel, different chassis geometry and increased suspension travel.

Note: ABS is not designed to shorten the braking distance. Please always ride at a safe speed for road and weather conditions, including while cornering.



Bi-directional Quick Shift System

This standard-equipment feature lets you shift up or down without operating the clutch lever. When activated, the system delivers clean, silky smooth upshifts with uninterrupted acceleration. Downshifts are also quick and smooth, thanks in part to automatic hands-free blipping and engine braking working together harmoniously.



Cruise Control System

Cruise control reduces fatigue when travelling long distances at constant speeds by letting you maintain a set speed without operating the throttle. The system now allows settings when riding in 2nd gear or higher at engine speeds between 2,000rpm and 7,000rpm, which translates to vehicle speeds of roughly 25km/h to 160km/h. The handy resume function re-engages the system and returns to the most recent speed setting after cancelling.



Suzuki Traction Control System (STCS)

Designed to help prevent the rear wheel from slipping, this system reduces stress and fatigue while instilling greater confidence in controlling your ride. You can select from 3 modes to control how quickly the system takes effect and how proactive it is in limiting wheel spin, or you can opt to run with it turned off.

Note: The traction control system is not a substitute for the rider's throttle control. It cannot prevent loss of traction due to excessive speed when the rider enters a turn and/or applies the brakes. Neither can it prevent the front wheel from losing grip.



Motion Track Brake System

Vehicle posture data from the IMU is combined with front and rear wheel speed sensor data to allow ABS activation, even when leaning into corners. This helps maintain traction and lean angle so you can better trace your intended line through the corner. Mode 1 provides minimal intervention, while Mode 2 intervenes more proactively.

Note: ABS is not designed to shorten the braking distance. Please always ride at a safe speed for road and weather conditions, including while cornering.





Suzuki Drive Mode Selector (SDMS)

Freely choose between three different power output characteristic modes to best match varying riding conditions or your preferences. While all three ultimately deliver maximum engine output, finer control over the level of throttle response and torque characteristics when accelerating empowers you to ride with greater confidence and pleasure.



Hill Hold Control System

This system automatically engages the rear brake for 30 seconds after coming to a stop while facing uphill on an incline, even when you release the brake lever or pedal. This helps ensure a smother restart free of worries that the bike will roll backward.




Load Dependent Control System

This system recognizes changes in the load conditions of any given moment and responds by automatically adjusting brake pressure to provide stable braking regardless of the load you



Slope Dependent Control System

While constantly monitoring the motorcycle's posture and angle, the system controls brake pressure to prevent rear wheel lift and help achieve confident braking, even riding downhill



This cable-free system leverages the onboard ECM to finely control the relationship between throttle action and engine output characteristics. Individual settings are tuned to match each of the SDMS modes and throttle grip action is optimized, particularly when first opening the throttle, to improve controllability and provide faithful response, especially when riding on gravel roads.

Suzuki Easy Start System

One quick press of a button lets you start the engine without pulling in the clutch lever. As a function used on every outing, Easy Start makes your riding experience all the more pleasurable and convenient.

Low RPM Assist

By helping maintain engine idle speed for smoother and easier starts, this function helps you operate and control the bike more easily in stop-and-go traffic.



2002 First Generation

ntroduced as a new-generation sports adventure tourer, the original Strom 1000 won the hearts of



2014 Second Generation

Innovations included the first application of traction control on a Suzuki production motorcycle, distinctive new styling, and enhanced performance that evolved it into a -round adventure tourer.



Suzuki released the V-STROM 1050/XT featuring sharper, more aggressive styling and a stronger, torquier engine. It also a collection of the latest electronic assist systems that help u ride with greater confidence and peace of mind.





Design is in our DNA

The DR-Z800 desert racer made design history when Suzuki entered it in the 1988 Paris-Dakar Rally, introducing a unique new concept to the rally scene that remains popular with motorcycle enthusiasts today. The DR-Z was compact, light and tough as nails. One of its most striking design elements had to be the radical new design expression of the prominent "beak" out front.

As evidenced by its modern interpretation of the "beak" design, The new V-STROM 1050/DE remains true to this heritage of Suzuki design DNA.

New V-STROM 1050/DE – The timeless virtue of fine design heritage

In marking the 20th anniversary of the popular series, the V-STROM 1050/DE evolves to deliver even greater freedom to explore all the excitement adventure touring has to offer, whether on the road or heading off to explore wilderness trails. In terms of design, this thoroughly modern interpretation of Suzuki's legendary DR-Z achieves a more aggressive yet sophisticated look with its straighter, sharper lines.



Breakout Performance Backed by Solid Core Strength

The V-STROM 1050/DE's compact, lightweight chassis is engineered to maximize agility, comfort, u reassuring riding pleasure. Every aspect reflects a focus on great handling and control in a wide range of real-world conditions, whether riding long distances on paved roads or heading down country trail results is the solid core strength needed to deliver stellar performance as an all-round adventure tourer. The new model offers you a choice of optimizations geared toward your preferences for pursuing differences types of adventure activities. While the V-STROM 1050 is engineered with a stronger focus on maximizing



KYB inverted front forks with 43mm inner tubes deliver a smooth. controllable ride and feature stable damping characteristics well suited to adventure touring. Fully adjustable, they allow you to match settings to your preference or intended use. The link-type monoshock KYB rear suspension contributes to agility and stability, and its preload can be adjusted by simply turning the dial by hand.

Reliable Stopping Power

A pair of Tokico radial mount monobloc callipers, each with four opposed pistons, act on 310mm floating-mount discs to provide sure stopping power in the front. These work in conjunction with the rear disc brake as part of the antilock braking system (ABS) that helps prevent the wheels from locking up for more stable braking.





Windscreen

The V-STROM 1050 windscreen's shape and size are designed to maximize comfort when touring for long distances. It features 50mm of vertical adjustment performed using a quick release handle. The V-STROM 1050DE adopts a smaller smoke-tinted windscreen designed to maximize visibility on country trails. Both windscreens were tested extensively to ensure they effectively cut wind noise and prevent buffeting for a more comfortable and less tiring riding experience.

Tapered Aluminium Handlebars

The tapered aluminium handlebars for the V-STROM 1050/DE are shaped to be comfortable to hold and engineered to offer the right degree of rigidity and optimal grip width to provide positive control, whether riding on or off paved roads. The V-STROM 1050DE handlebars use thicker tubing and a softer grade aluminium so they flex just the right amount and better absorb bumps to make exciting runs on rough ground easier on your hands and arms. They also feature an even wider grip that enhances controllability, particularly when standing on the pegs to negotiate rough surfaces.

The V-STROM 1050 features an independent rider and pillion seat design that is both visually appealing and achieves the right level of firmness to provide plenty of comfort with less fatigue on long rides. The rider seat height can be raised 20mm using an included height riser stored beneath the pillion seat. The V-STROM 1050DE adopts a fixed-height seat design that reduces weight while also achieving greater rigidity. This durable seat better stands up to input load when riding on unpaved surfaces, as well as to weight shifts as you change position to master the terrain.

Optional higher and lower seats are also available as genuine Suzuki accessories.

Nheels and Tyres with Purpose

The V-STROM 1050 rides on 10-spoke cast aluminium wheels shod with Bridgestone BATTLAX ADVENTURE A41 radial tyres. The 110/80R19 front and 150/70R17 rear tyres contribute to nimble handling and positive grip, whether the road surface is dry or wet. They provide a smooth ride and greater comfort when touring for long distances, and continue to inspire confidence even when you continue your adventure beyond where the pavement ends.

The V-STROM 1050DE takes advantage of wire-spoked wheels with aluminium rims to better endure the pounding when exploring trails and other rough surfaces. It also adopts a larger 21-inch front rim for greater stability and better control on gravel and flat dirt. Both wheels are shod with Dunlop TRAILMAX MIXTOUR tyres, which feature a semi-block tread pattern and custom-designed internal structure that deliver the solid traction and performance you want when exploring open trails.

For those who wish to head further off the beaten track


The V-STROM 1050DE introduces a new package of features aimed specifically at maximizing performance and control on gravel and flat dirt.

- Its dedicated chassis geometry is designed to deliver greater stability and controllability on gravel or flat dirt, while providing a comfortable riding position and well-balanced front/rear weight distribution. Features include a 40mm longer wheelbase, a longer 27°30' trail, 25mm taller ground clearance and a 20mm wider handlebar grip on each side.
- This custom chassis geometry includes a new 21-inch front wheel and longer version of the V-STROM's rugged aluminium swingarm for greater straight-line stability and better control when tearing up gravel roads.
- The suspension adopts a longer stroke, with 170mm of front and 168mm of rear travel. The suspension's spring rate, valve, and piston settings are custom-tuned for riding on
- Its trail-ready gear includes a stronger drive chain, an aluminium engine protector, a standard-equipment accessory bar and wide steel footpegs designed for greater stability when standing while riding.

Proven Twin-Spar Alloy Frame


The pursuit of building top-performing aluminium frames has been an integral part of Suzuki's engineering DNA for decades, and the frame for the V-STROM 1050/DE remains true to this heritage. It incorporates aluminium castings and extruded aluminium sections to lend the right amount of proven reliability that delivers excellent straight-line stability, handles brilliantly and is easy to manoeuvre, wherever your journey takes you.

suppleness and strength to an overall rigid alloy structure. It also features updated seat rails that better support the input load from unpaved surfaces. The result is a trim, light and strong frame of tried and















Transmission

The six-speed transmission features updated gear ratios. The new ratio for first gear makes shifting from first through fifth gears smoother, makes acceleration faster, and improves controllability. Sixth gear was also updated to make riding at highway speeds more comfortable and enjoyable. The new ratios also contribute to smooth operation of the Bi-directional Ouick Shift system.

Suzuki Clutch Assist System (SCAS)

SCAS delivers sure operation and a light touch to clutch lever operation that helps reduce left hand fatigue. At the same time, it ensures positive power transfer when accelerating and smoother deceleration when downshifting, advantages it also brings to the new Bi-directional Ouick Shift system as well.



Sodium-filled exhaust valves

response and stable idle.

Hollow sodium-filled exhaust valves help reduce the temperature in the combustion chamber.

This not only results in better loading efficiency and a better feeling to engine operation, it also contributes to improving the durability of the valves.

Each cylinder utilizes two iridium spark plugs. The primary plug fires throughout the engine's rpm range, while the secondary

plug helps improve combustion efficiency and power delivery

at low rpm. This technology also contributes to linear throttle



Forged pistons

The V-twin engine uses highly-rigid, lightweight forged pistons. The heads are anodized and conical machining inside the wrist pin holes transfer load and mitigate stress transferred to the crowns. Both these treatments contribute to enhanced durability.



Electronic Throttle Bodies

Each of the two cylinders is fed by independent 49mm large bore electronic-controlled throttle bodies. The butterfly valve of each throttle body is opened and closed independently to achieve more precise throttle control and help realize more stable idling.



Tuned Exhaust System

The 2-into-1 exhaust system produces a pleasing note that befits the V-twin engine. Better yet, the high-efficiency catalytic converter inside the collector helps comply with Euro 5 emission standards, while at the same time maximizing power output and overall performance.



Colour Multi-information Instrument Cluster

The V-STROM 1050/DE adopts a custom new 5-inch colour TFT LCD multifunction instrument panel that features clearly legible information displays. High-quality displays keep you fully aware of all the bike's systems and settings, and supply vital real-time operating status

information. The tachometer does double duty as a programmable rpm indicator light that blinks when the engine reaches a preset speed, and the LCD now adds a function that lets you display large pop-up alerts and warnings. Manual or automatic switching settings for the day (white) and night (black) display modes let you maximize visibility at any hour and in any riding situation.



The ergonomic switch layout maximizes operating ease and efficiency so you can access all controls while focusing on the road ahead. Select modes and make settings and adjustments for each S.I.R.S. systems by simply operating the MODE and UP/DOWN switches on the left handlebar. In addition, you can quickly engage or resume cruise control using a dedicated button on the right handlebar switch.



USB Port and 12V DC Outlet

A USB port built into the left side of the multifunction instrument panel lets you recharge your smartphone. There is also a 12V DC outlet under the seat that can be used to charge or power a variety of devices.

- * Using the USB port while the engine is idling or stopped may drain the battery. Be aware of battery drain when using the USB port.
- * Failure to observe the following items when handling the USB port may result in damage to the motorcycle or connected devices.
 - Do not connect any electronic device other than a mobile phone.
 - Do not use when washing the motorcycle or when it is raining.

 - * Reattach the cap when the port is not in use.

LED Lighting

Vertically stacked rectangular LED headlights provide you with a clear view of the road ahead, while at the same time adding stylish flair to the face of the V-STROM 1050/DE. Compact LED position lights, LED turn signals and LED tail light ensure clear visibility and practical durability.











Top and side cases

These rugged, weather-resistant cases allow you to carry all your gear for a long outing, and are designed to not interfere with the V-STROM 1050/DE's handling or stability, even with loaded cases attached.

Aluminium top case: Max loading 3kg and case capacity 38L.
Aluminium side case set: Max loading 3kg and case capacity 37L each.
Please use these items in the speed less than 130km/h.



Low and high seat options

Low seats available for the V-STROM 1050 and V-STROM 1050DE lower seat height by approximately 30mm to offer more riders greater control and confidence when the bike is stopped. The V-STROM 1050DE also offers a high seat option that raises seat height by approximately 30mm.



Grip heater

Heats the entire surface of the grips and offers three levels of heat settings provide greater comfort to match a wide variety of riding conditions.



LED Fog Lamp Set

This bright LED fog lamp attaches firmly to the accessory bar* to provide better visibility when riding in inclement conditions, and to heighten the appeal of the bike's adventure styling.

*The accessory bar is standard equipment on the V-STROM 1050DE and is available as a genuine accessory for the V-STROM 1050.

